

Hydraulic Tools

NEW FOR 2012!

Hand Held Core Drills

RGC Hand Held Core Drills are the answer to safe, easy, non-percussive drilling through concrete and aggregates with or without reinforcing. The light, compact and quiet design permits easy handling, which makes these drills ideal for use in confined spaces. Neat, clean and damage-free holes are the result of superior power, speed and hydraulic action. A 1/2 in. to 5/8 in. adapter is available.

HHCD Specifications

Model	HHCD104	HHCD214
Flow	5 gpm (19 lpm)	5 gpm (19 lpm)
Press. Range	1450 - 2450 psi (100 - 170 bar)	1450 - 2450 psi (100 - 170 bar)
Speed @ 5 gpm	1500 rpm	600 rpm
Weight	17 lbs (7.7 kg)	17 lbs (7.7 kg)
Core Bit Dia.	1 - 4 in. (2.5 - 10.2 cm)	2 - 14 in. (5.1 - 35.6 cm)
Drive	1-1/4 UNC	1-1/4 UNC



HHCD214 Hand Held Core Drill

HB20 HydraBreaker

RGC's HB20 HydraBreaker is a 20 lb. class lightweight chipping breaker with a higher performance-to-weight ratio than other hydraulic or pneumatic breakers. It operates at 5 gpm @ 2000 - 2250 psi; hose whips andmoil point are included.

Continuous lubrication reduces component wear, minimizes maintenance and extends product life. Absence of dust producing exhaust and noise provides a cleaner, quieter and more efficient operation. The HB20 is lighter weight (22 lbs.) and more portable than pneumatic systems.



HB20 HydraBreaker

7/16 in. Impact Wrenches

RGC's hydraulic 7/16 in. Impact Wrench has a Quick Change Chuck and is available with or without adjustable torque settings. Each provides lightweight, quiet and efficient operation in a compact design. These tools are ideal for a variety of construction, municipal and utility applications. A 7/16 in. hex to 1/2 in. square drive adapter is available.

7/16 in. Impact Wrench Specifications

Model	7/16 " Wrench	7/16" Wrench
Chuck Type	Hex Head Quick Change	Hex Head Quick Change
Pressure	1000 - 2500 psi (69 - 170 bar)	1000 - 2500 psi (69 - 170 bar)
Flow	4 - 10 gpm (15 - 38 lpm)	4 - 12 gpm (15 - 45 lpm)
Operation	Open- or Closed-Center	Open- or Closed-Center
Torque	400 ft-lb @ 8 gpm	Adjustable 80 - 400 ft-lb.
Weight	7.1 lbs. (3.2 kg)	7.1 lbs. (3.2 kg)



7/16 in. Impact Wrench



REIMANN & GEORGER CORPORATION

RGC Construction Products Are Distributed By:

1849 Harlem Road • Buffalo, NY • 14212

Phone: 716-895-1156 • Fax: 716-895-1547

Toll Free: 800-RGC-TOOL (742-8665) • www.rgcproducts.com

©2012 Reimann & Georger Corporation. All rights reserved.