

Swing Hoist HydraPaks

Swing Hoist HydraPaks

RGC® HydraPaks are portable, lightweight power sources that put reliable, efficient hydraulic power at your Swing Hoist job site. They are easily transported to the job site in the back of a pick up truck or van.

HydraPaks are cart-mounted, equipped with a lifting eye, 16 in. pneumatic tires and are available in gas and electric models. Each unit has low oil engine shutdown, a heavy-duty heat exchanger and 6 gallon hydraulic reservoir.



HV1658S HydraPak

Features and Benefits

- Compact, lightweight hydraulic power source for RGC Swing Hoists.
- Cart-mounted with large 16 in. pneumatic tires for easy transporting.
- Low noise level.
- Easy maintenance and parts replacement.
- Electric start and low oil shutdown on all models.
- Controls easily accessible for safety and comfort.
- Powder-coated tubular steel frame protects unit from damage.
- Detachable handles for easy transporting and storage.
- 12V battery included.
- Lifting eye and 6 gallon oil reservoir.
- Heavy duty 8-tube heat exchanger on most models.
- The HV1858S is equipped with an 18 hp B & S Vanguard gas engine with Performance Control™ electronic governor.
- Swing Hoist HydraPaks can be used to power hydraulic tools, such as saws, breakers and pumps.

Swing Hoist HydraPak Specifications

Model	HR96S	H1058S	HH1158S	HH1358S	HR1458S	HV1658S	HV1858S	HE7558S
Engine	Robin 9 hp	B&S 10 hp Intek I/C engine	Honda 11 hp	Honda 13 hp	Robin 14 hp	B&S 16 hp Vanguard V-Twin	B&S 18 hp Vanguard V-Twin w/ Auto Idle	Baldor 7-1/2 hp 3 ph electric motor
Flow	6 gpm (23 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)
Operating Pressure (max)	1800 psi (124 bar)	2000 psi (138 bar)	2000 psi (138 bar)	2250 psi (155 bar)	2250 psi (172 bar)	2500 psi (172 bar)	2250 psi (155 bar)	2000 psi (138 bar)
Hour Meter	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pull Start	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Electric Start	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Winch & Boom Valves	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Weight	283 lbs (128 kg)	305 lbs (138 kg)	312 lbs (142 kg)	324 lbs (147 kg)	141 lbs (136 kg)	300 lbs (136 kg)	300 lbs (136 kg)	304 lbs (138 kg)



REIMANN & GEORGER CORPORATION

P.O. Box 681 • Buffalo, NY • 14240-0681 • Phone: (716) 895-1156 • Fax: (716) 895-1547

Toll Free: 800-831-LIFT (5438) • Web: www.rgcproducts.com

©2009/15 Reimann & Georger Corporation. All rights reserved.